SBM 55s



Full Featured Compact
Wheel Balancer

Unbalanced to 0.00's in **ONE SPIN**

The Ultimate Space Saver Balancer

2 Dimension Automatic Entry With Stick-On Weight Applicator

Hidden Weight Spoke Mode

Foot Brake for Precise Weight Placement

Quick-Nut Standard

Long 40mm Shaft Accommodates Flange Plates, Motorcycle Wheels & Wide Wheel Assemblies

Engineered for High Volume Tire Shops



SEE VIDEO DEMONSTRATIONS AT WWW.GRPEQUIP.COM





Unique Space
Saving Hood
Design Allows
the Balancer to
Be Positioned
Only 11" From
the Wall



Precision Stick-On Weight Placement with ALU Data Arm

Optional Accessories



Open Center Offset Spacer

<u>Allows Back-Coning of</u>

<u>Truck & SUV Wheels for an</u>

<u>Accurate Balance</u>



Two-Sided Truck Cone
For Light/Medium Trucks
& SUV's

606300

Voltage	Max Wheel Weight	Max Tire Diameter W/Hood	Max Tire Diameter WO/Hood	Max Rim Width	Max Rim Diameter	Max Rim Diameter For Weight Applicator
110 Volt	150 Lbs.	33"	44"	20"	30"	26"

^{* 4} Cone Set Standard

GRP Enterprises LLC.
PO Box 6700
11011 Leadbetter Rd.
Ashland, VA 23005
(804) 365-7959 FAX (772)402-4548
www.grpequip.com

