



WB670

Full Featured, High Volume
Video Wheel Balancer

From Unbalanced To 0.00's
in **ONE SPIN**

Graphics Display Proper
Procedures

3 Dimension Automatic
Entry With Stick On
Weight Applicator

AUTOMATIC Hidden
Weight Spoke Mode

Foot Brake For Precise
Weight Placement

Quick Nut Standard

Long 40mm Shaft
Accommodates Flange
Plates, Motorcycle Wheels
And Wide Wheel Assemblies

Engineered For High
Volume Tire Shops



**Designed For
Alloy Wheels**

SEE VIDEO DEMONSTRATIONS AT
WWW.GRPEQUIP.COM



Photo Eye For Automatic
Hidden Spoke Mode



Precision Stick On Weight
Placement With ALU Data Arm



Optional Laser To Detect Radial
Run-Out



Optional Accessories



606200

Open Center Offset Spacer
Allows Back Coning Of
Truck And SUV Wheels For
An Accurate Balance



606300

Two Sided Truck Cone
For Light/Medium Trucks
And SUV's

Voltage	Max Wheel Weight	Max Tire Diameter	Onboard Adaptor Storage	Max Rim Width	Max Rim Diameter	Max Rim Diameter For Weight Applicator
110 Volt	150 Lbs.	44"	7	20"	30"	26"

* 4 Cone Set Standard

GRP Enterprises LLC.
PO Box 6700
11011 Leadbetter Rd.
Ashland, VA 23005
(804) 365-7959 FAX (772)402-4548
www.grpequip.com

